

BYT.2a-32 DC Isolator Switches

- BYT.2a-32 Rated Voltage 1200V DC
- DIN Rail Mounting
- OFF Lockable
- Flame-Retardant
- Arcing Time < 3ms
- IEC60947-3
- 4 Poles(Single|Double Strings Available)
- DC-21B: 16A, 25A, 32A up to 1200V DC



Welcome to our website for more information:
www.zjbeny.com



Leading Manufacturer for
PV Solution

Wiring Diagram

Contacts wiring diagram	500V	600V	800V	1000V	1200V	Poles in series	Number of Strings	Type Number	Weight kg/PCS
	16A	16A	16A	9A	7.5A	2	1	BYT.2-16 DR2	0.24
	25A	25A	20A	11A	9A	2	1	BYT.2-25 DR2	0.24
	32A	32A	23A	13A	10A	2	1	BYT.2-32 DR2	0.24
	29A	29A	16A	9A	7.5A	2	1	BYT.2-16 DR2H	0.30
	45A	45A	20A	11A	9A	2	1	BYT.2-25 DR2H	0.30
	58A	50A	23A	13A	10A	2	1	BYT.2-32 DR2H	0.30
	16A	16A	16A	9A	7.5A	2	2	BYT.2-16 DR4	0.27
	25A	25A	20A	11A	9A	2	2	BYT.2-25 DR4	0.27
	32A	32A	23A	13A	10A	2	2	BYT.2-32 DR4	0.27
	16A	16A	16A	16A	16A	4	1	BYT.2-16 DR4S	0.28
	25A	25A	25A	25A	25A	4	1	BYT.2-25 DR4S	0.28
	32A	32A	32A	32A	32A	4	1	BYT.2-32 DR4S	0.28
	16A	16A	16A	16A	16A	4	1	BYT.2-16 DR4B	0.28
	25A	25A	25A	25A	25A	4	1	BYT.2-25 DR4B	0.28
	32A	32A	32A	32A	32A	4	1	BYT.2-32 DR4B	0.28
	16A	16A	16A	16A	16A	4	1	BYT.2-16 DR4T	0.28
	25A	25A	25A	25A	25A	4	1	BYT.2-25 DR4T	0.28
	32A	32A	32A	32A	32A	4	1	BYT.2-32 DR4T	0.28

Switching Configurations

Type	2-pole	2-pole 4 Paralleled Poles	4-pole	4-pole with Input on top Output bottom	4-pole with Input and Output bottom	4-pole with Input and Output on top
BYT.2-16	2	2H	4	4S	4B	4T
BYT.2-25	2	2H	4	4S	4B	4T
BYT.2-32	2	2H	4	4S	4B	4T
Contacts Wiring graph						
Switching example						

Dimensions(mm)

