



- 1 Waterproof Plug
- 2 IP66 Ingress Protection
- 3 Sealed Plug
- 4 Knob
- 5 Brand
- 6 ON
- 7 OFF



BYH-32



Accessories


Application

BENY BYH Series DC Isolator Switch in plastic enclosure is applied 1~20KW Residential or Commercial Photovoltaic system, placed between photovoltage modules and inverters. Arcing time less than 3ms, that keep solar system more safe. To ensure its stability and long service life, our products are made by components with optimum quality. Max voltage up to 1000V DC It holds a safe lead among similar products.

Feature

- IP66 , UV Resistance
- Arcing Time < 3ms
- Earth Terminal
- IEC60947-3, AS60947.3
- 2 Pole, 4 Poles Available(Single | Double String)
- DC-PV2 / DC-21B: 32A up to 1000VDC

Appearance Introduction



Parameter

Electrical Characteristics

| | |
|--|--|
| Type | BYH-32, BYH-32M1, BYH-32M2 |
| Function | Isolator, Control |
| Standard | IEC60947-3, AS60947.3 |
| Utilization category | DC-PV2 / DC-21B |
| Pole | 4P |
| Rated frequency | DC |
| Rated operational voltage (U_o) | 500V, 600V, 800V, 1000V |
| Rated operational current (I_o) | See the next page |
| Rated insulation voltage (U_i) | 1200V |
| Conventional free air thermal current (I_{th}) | // |
| Conventional enclosed thermal current (I_{the}) | Same as I_o |
| Rated short-time withstand current (I_{sw}) | 1kA, 1s (4, 4S, 4B); 1.7kA, 1s (2H) |
| Rated short-time making capacity (I_{cm}) | 1.7kA, 1s (4, 4S, 4B); 3kA, 1s (2H) |
| Rated conditional short-circuit current (I_{cn}) | 3kA |
| Rated impulsed withstand voltage (U_{imp}) | 8.0kV |
| Overvoltage category | II |
| Suitability for isolation | Yes |
| Polarity | No polarity, "+" and "-" polarities could be interchanged. |

Service Life/Cycle Operation

| | |
|------------|-------|
| Mechanical | 20000 |
| Electrical | 2000 |

Installation Environment

| | | |
|----------------------|----------------------------|------|
| Ingress Protection | Enclosure | IP66 |
| | Switch body | IP20 |
| Storage Temperature | -5°C ~ +85°C | |
| Mounting Type | Vertically or horizontally | |
| Pollution degree | 3 | |
| Suitable environment | Outdoor / Indoor | |

BYH Series PV DC Isolator Switches

| Identification | Rating data | | |
|--|--|---|---|
| Switch, unenclosed - catalogue number (with DC-PV2 rating) | BYH.1-32, BYH.2-32 | | |
| Specific dedicated individual enclosure - catalogue number (with minimum IP56NW rating) | BYH-32 IP66NW | | |
| Assembly of switch and specific dedicated individual enclosure - catalogue number | / | | |
| I_{th} rated thermal current, unenclosed, at 40°C shade ambient air temperature | 32 amps | | |
| I_{the} rated thermal current, indoors, at 40°C shade ambient air temperature, in a specific dedicated enclosure | 32 amps | | |
| I_{the} rated thermal current <u>outdoors</u> at 40°C shade ambient air temperature <u>without solar effects in</u> a specific dedicated enclosure rated IP66NW | 32 amps | | |
| I_{the} solar current value outdoors at 60°C shade ambient air temperature (see D.8.3.11, table D3), with solar effects in a specific dedicated enclosure rated IP66NW | 29 amps | | |
| | U_e rated operational voltage DC Volts | I_e ; DC-PV2 rated operational current Amps | $I_{(make)}$ and $I_{c(break)}$ DC-PV2 4 x I_e Amps |
| 2 pole (<u>1</u> / <u>2</u> / <u> </u>) | ≤500 | 32 | 128 |
| | 600 | 13 | 52 |
| | 800 | 9 | 36 |
| | 1000 | 9 | 36 |
| 4 pole (<u>1</u> / <u>2</u> / <u>3</u> / <u>4</u> / <u> </u>) | ≤500 | 32 | 128 |
| | 600 | 32 | 128 |
| | 800 | 32 | 128 |
| | 1000 | 32 | 128 |

NOTE 1 The rating data in the table is example data, it is intended to be replaced by the relevant actual data.

NOTE 2 The ratings section of this table for U_e , I_e and $I_{(make)}$ and $I_{c(breaker)}$ may have other number of poles or pole configurations than that shown, based on the test evidence obtained.

NOTE 3 The other data required in D.5.2.4 need not be in a table format.

BYH Series PV DC Isolator Switches

Wiring Diagram for Rated operational voltage U_e (V) & Rated operational current I_e (A)


| Contacts wiring diagram | 500V | 600V | 800V | 1000V | Poles in series | Number of Strings | Type Number | Weight kg/PCS |
|-------------------------|------|------|------|-------|-----------------|-------------------|-------------|---------------|
| | 32A | 13A | 9A | 9A | 2 | 2 | 4 | 0.70 |
| | 40A | / | / | / | 2 | 1 | 2H | 0.70 |
| | 32A | 32A | 32A | 32A | 2 | 1 | 4B | 0.70 |
| | 32A | 32A | 32A | 32A | 4 | 1 | 4S | 0.70 |

Switching Configurations


| Type | 4-pole | 2-pole 4 Paralleled Poles | 4-pole with Input and Output bottom | 4-pole with Input on top Output bottom |
|--------------------------|--------|---------------------------------|---|--|
| / | 4 | 2H | 4B | 4S |
| Contacts Wiring graph | | | | |
| Switching example | | | | |

Bridging links installation

installed incorrectly



installed correctly



* Please note that all connections (including bridging link connections) should be tightening before energization.

BYH Series PV DC Isolator Switches

Terminals / connection

| | | |
|--|---|--|
| Type | BYH-32, BYH-32M1, BYH-32M2 | |
| Number of poles | 4-pole | |
| Terminal designation, main circuit | 1; 3; 5; 2; 4; 6; 7; 8 | |
| Type of terminal, main circuit | Screw terminal | |
| Rated cross section area, main circuit | 4.0-16mm ² | |
| Type of onductor |  | 4-16mm ² (Rigid: Solid or Stranded) |
| |  | 4-10mm ² (Flexible) |
| Number of conductors per terminal | 1 | |
| Required preparation of the conductor | Yes | |
| Stripping length (mm), main circuit | 8mm | |
| Tightening torque (M4), main circuit | Min: 1.2Nm | |
| | Max: 1.8Nm | |

Dimensions(mm)

